FLC301 Space frame





Description

IP66. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.


Including terminal box, for mounting on \emptyset 48-60 mm pipes or space frames.


Mains voltage versions only, ON-OFF Class I or DALI interface available on request (converter in thermally-separated compartment); refer to accessory listings.

Weight	1.70 kg	
Light distribution	symmetric, very narrow beam [EE]	
Light source	LED-1/6W / 500 mA - 4000 K	
CRI	80	
Power supply	EC	
LEDs	1	
Rated input power	7.5 W	
Rated lumens (lm)		
LED Lumen	610.6	
Total Lumen	610.6	
Та	25	
Nominal Lumen (lm)		
LED Lumen	720	
Total Lumen	720	
Тс	25	

we-ef

FLC301 Space frame





Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime Ta=25° L90B10 > 90000h

WE-EF LIGHTING Pty Ltd


we-ef

FLC301 Space frame

Optical Accessories

Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	145-7229	42.5



Wallwash lens

Description Par	C1
Vallwash lens IO-20 14	42.5




Honeycomb louvre

WE-EF LIGHTING Pty Ltd


145-7296



FLC301 Space frame



Glare shield




Snoot

145-7296



FLC301 Space frame



145-7296

FLC301 Space frame



Control

DALI interface

Description	Part ID	Additional information
DALI interface 430-0013	430-0013	DALI variant. The luminaire is equipped with a DT6 Dali driver (Dali 2.0).
		Dali 2.0 -Application controllers and Input devices defined -Single-masters and multi-masters allowed -Event priorities defined -Separate addressing & grouping from control gear
		Note: Mixing Dali 1 and Dali 2.0 drivers can cause problems because the addressing and the command scope has changed!



145-7296 FLC301 Space frame

WE-EF LIGHTING Pty Ltd

6/13 Downard Street, 3195 Braeside, Victoria Phone: +61 3 8587 0444 Fax: +61 3 8587 0499 info.australia@we-ef.com https://we-ef.com/aus

Subject to technical changes and errors. Generated on 23/10/2024

