ETV140 LED



Description

IP67*, Class I. IK08. Marine-grade all aluminium construction. Anodized aluminium extrusion. PCS hardware. Silicone rubber gasket. Safety glass lens. Luminaire can be driven over at low speed, without accelerating or turning, by vehicles with air-filled tyres, at a weight up to 5 tonnes per wheel. Max. static load, 3 tonnes (according to DIN EN 60598-2-13). Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible cable, including sealable junction box SJB. Linear PMMA LED lens. Factory installed LED circuit board. LED board can be easily removed for upgrading. Luminaire is factory sealed and does not need to be opened during installation. Integral electronic converter with DALI interface in thermally-separated compartment. Luminaires with [LB/ IW] [LM/IW] and [LE/IW] light distribution are supplied with honeycomb shield IW to reduce stray light.

Optional 2200 K version available. To be specified at time of ordering.

The optional installation blockout is recommended for mounting. To be ordered separately.

The luminaire is not suitable for permanent underwater operation and must be switched off in the event of flooding.

Weight	7.50 kg
Light distribution	symmetric linear, narrow beam [LE/IW]
Light source	LED-64/40W / 225 mA - 3000 K
CRI	80
Power supply	EC
LEDs	64
Rated input power	44 W
Nominal Lumen (lm)	
LED Lumen	90
Total Lumen	5760
Tj	85
Rated lumens (lm)	
LED Lumen	34.8
Total Lumen	2227.4
Та	25

WE-EF LEUCHTEN GmbH

ETV140 LED




* Additionally tested to IP66, IP67, IP68 0.1 bar 3h, up to 1 m depth according to DIN EN 60598 and IP69K/80° according to DIN EN 60529.

ETV140 LED







Specifications

Material description

Body Marine-grade all aluminium construction. Anodized aluminium extrusion.

Lens Safety glass lens

Colours

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP67
Impact resistance IK08

Electrical description

Power supply 220-240V / 50-60 Hz

Driver / Ballast DALI
Power factor > 0.9
Surge protection 1/2 kV

Additional information

Lifetime Ta=25° L90B10 > 90000h

Energy efficiency class D (Light source)

WE-EF LEUCHTEN GmbH


ETV140 LED



Electrical Accessories

Sealable junction box

Description	Part ID	C1	M1	M2
Sealable junction box SJB130	185-1624	146	Ø 10	Ø 12 - 19




ETV140 LED



Optical Accessories

Honeycomb louvre



ETV140 LED




Mounting Accessories

Installation blockout, Type I

Description	Part ID	А	C1	D1	D2	Weight (kg)
BEV140-I-1/1227 (1 luminaire)	186-0314	1275	160	55	120	6.10



BEV140-I-2/1227	(2 luminaires)	186-0315	2504	160	55	120	11.70



WE-EF LEUCHTEN GmbH

ETV140 LED



Description	Part ID	А	C1	D1	D2	Weight (kg)
BFV140-I-3/1227 (3 luminaires)	186-0316	3733	160	55	120	17.40



BEV140-I-4/1227 (4 luminaires) 186-0317 4962 160 55 120 23





186-0408 ETV140 LED

WE-EF LEUCHTEN GmbH

Töpinger Straße 16, 29646 Bispingen, Germany Phone: +49 5194 909-0

> info@we-ef.com https://we-ef.com

Subject to technical changes and errors. Generated on 23/10/2024

