




**Description**

IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths, 190 mm and 300 mm available on request.

|                           |                              |
|---------------------------|------------------------------|
| Weight                    | 3.00 kg                      |
| Light distribution        | symmetric, medium beam [M]   |
| Light source              | LED-12/24W / 700 mA - 3000 K |
| CRI                       | 80                           |
| Power supply              | EC                           |
| LEDs                      | 12                           |
| Rated input power         | 27 W                         |
| <b>Nominal Lumen (lm)</b> |                              |
| LED Lumen                 | 290                          |
| Total Lumen               | 3480                         |
| Tj                        | 85                           |
| <b>Rated lumens (lm)</b>  |                              |
| LED Lumen                 | 257.4                        |
| Total Lumen               | 3088.2                       |
| Ta                        | 25                           |



## Specifications

### Material description

|                      |   |
|----------------------|---|
| Body                 | Marine-grade, all aluminium construction  |
| Lens                 | Safety glass lens   |
| Colours              | <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: black; margin-right: 5px;"></div> <div style="margin-right: 10px;">RAL9004 Signal black</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #cccccc; margin-right: 5px;"></div> <div style="margin-right: 10px;">RAL9006 White aluminium</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #808080; margin-right: 5px;"></div> <div style="margin-right: 10px;">RAL9007 Grey aluminium</div> </div> <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: #e0e0e0; margin-right: 5px;"></div> <div style="margin-right: 10px;">RAL9016 Traffic white</div> </div> |
| Gasket               | Silicone CCG® Controlled Compression Gasket   |
| Fasteners            | PCS Polymer Coated Stainless Steel Hardware   |
| Ingress protection   | IP66  |
| Impact resistance    | IK07  |
| Corrosion resistance | 5CE+Primer  |

### Electrical description

|                  |   |
|------------------|---|
| Driver / Ballast | Integral EC electronic converter in thermally-separated compartment |
| Power factor     | >0.9  |

### Additional information

|          |                        |
|----------|------------------------|
| Lifetime | Ta=40° L90B10 > 90000h |
|----------|------------------------|

## Optical Accessories

### Linear spread lens

| Description       | Part ID  | Additional information  | C1  |
|-------------------|----------|---|-----|
| IO-180-DAC120-LED | 134-2000 | Broadens light distribution in one plane only. Ideally suitable for [M][EE][EES]. Does not fit in combination with [B] lens.<br>A maximum of one internal optical accessory. Internal component, factory installed. | 130 |




**Honeycomb louvre**

| Description   | Part ID  | Additional information   | C1  |
|---------------|----------|--|-----|
| IW-DAC120-LED | 134-2002 | Honeycomb louvre, matt black Teflon® coated. For luminaires equipped with [B] [M] light distribution.<br>A maximum of one internal optical accessory. Internal component, factory installed. | 103 |



**Wallwash lens**

| Description         | Part ID  | C1 |
|---------------------|----------|----|
| IO-20-WW-DAC120-LED | 134-2001 | 92 |



**134-2162**

**DAC120 LED**

**we-ef**

## Mounting Accessories

### Adaptor for side conduit entry

---

| Description                           | Part ID  | A  | C1  |
|---------------------------------------|----------|----|-----|
| DA12 Adaptor for DAC120/DAS120-<br>PM | 134-2108 | 31 | 140 |

---

