



Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. One cable entry, optional T-QPD connector for through wiring available on request. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Includes cable connector, for cable 2-12 mm. \pm 10° adjustable to compensate for sloping catenary systems.


Other standardised housing lengths available on request.

Optional 2200 K version available. To be specified at time of ordering.

Weight	7.20 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-24/48W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W
Nominal Lumen (lm)	
LED Lumen	270
Total Lumen	6480
Tj	85
Rated lumens (lm)	
LED Lumen	241
Total Lumen	5785.2
Та	25







Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

PCS Polymer Coated Stainless Steel Hardware **Fasteners**

Ingress protection **IP66**

IK07 Impact resistance

Corrosion resistance 5CE+Primer 0.0611 m² Windage

Electrical description

Driver / Ballast Standard. DALI on request

Power factor > 0.9

Additional information

Lifetime $Ta=40^{\circ} L90B10 > 90000h$

WE-EF LIGHTING Pty Ltd



Optical Accessories

Linear spread lens


Description	Part ID
IO-180-DAC140-LED	134-2064



Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	







Honeycomb louvre

Description	Part ID
IW-DA_140-LED	134-2066

