we-ef

DAS140 LED



Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable entry, second cable entry for through wiring with cable connector optional. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire. The luminaire is factory-sealed and does not need to be opened during installation.

Optional 2200 K version available, to be specified at time of ordering.

Includes cable connector, for cable 0.08-0.47 inch. +/- 10° adjustable to compensate for sloping catenary systems.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

15.87 lb
symmetric, very narrow beam, 'sharp cut-off' [VNS]
LED-24/48W / 700 mA - 2700 K
80
electronic gear
24
54 W
270
6480
85
241
5785.2
25

WE-EF LIGHTING USA, LLC


DAS140 LED


we-ef

For DarkSky compliant configurations of this product, please find the spec sheet and DarkSky certificate in the library.

DAS140 LED







Specifications

Material description

Body Marine-grade, die-cast aluminum alloy

Lens Safety glass lens

Colors

RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Windage 0.0611 m²

Electrical description

Driver / Ballast Standard. DALI on request

Power factor > 0.9

WE-EF LIGHTING USA, LLC

DAS140 LED



Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	Contact WE-EF USA for ETL/UL certification status.

DAS140 LED



Optical Accessories

Linear spread lens

Description	Part ID	
IO-180-DAC140-LED	134-2064	



Wallwash lens





Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	



Honeycomb louvre

Description	Part ID	
IW-DA 140-LED	134-2066	



WE-EF LIGHTING USA, LLC

134-2285 DAS140 LED

WE-EF LIGHTING USA, LLC

410-D Keystone Drive, 15086 Warrendale, PA 15086 Phone: +1 724 742 0030

> customersupport.usa@we-ef.com https://we-ef.com/us

Subject to technical changes and errors.

Generated on 10/23/2024

