

Description

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DMX interface.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)


| Weight | 5.50 lb |
|-----------------------|-------------------------------------|
| Light distribution | symmetric, wide beam [W] |
| Light source | LED-24/42W / 325 mA - 2200-6000K |
| CRI | 80 |
| Power supply | electronic gear |
| LEDs | 24 |
| Rated input power | 51 W |
| Nominal Lumen (lm) | |
| LED Lumen | 230 |
| Total Lumen | 5520 |
| Tj | 85 |
| Delivered lumens (lm) | |
| LED Lumen | 166.4 |
| Total Lumen | 3993.5 |
| Та | 25 |

we-ef

DAC140 TW LED TUNABLE WHITE







Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Driver / Ballast DMX

134-2258



DAC140 TW LED TUNABLE WHITE

Additional information

| Lifetime | $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ |
|----------|--|
| | |

Listings Contact WE-EF USA for ETL/UL certification status.



DAC140 TW LED TUNABLE WHITE

Optical Accessories

Linear spread lens

| Description | Part ID |
|-------------------|----------|
| IO-180-DAC140-LED | 134-2064 |





DAC140 TW LED TUNABLE WHITE

Wallwash lens

| Description | Part ID |
|---------------------|----------|
| IO-20-WW-DAC140-LED | 134-2065 |



Honeycomb louvre

| Description | Part ID | |
|---------------|----------|--|
| IW-DA_140-LED | 134-2066 | |





DAC140 TW LED TUNABLE WHITE

Mounting Accessories

Adaptor for side conduit entry

