

## DAS140 TW LED TUNABLE WHITE

**Description**

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. One cable entry, second cable entry for through wiring with cable connector optional. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DALI interface. The luminaire is factory-sealed and does not need to be opened during installation.

Includes cable connector, for cable 0.08-0.47 inch. +/- 10° adjustable to compensate for sloping catenary systems.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)  
+ XXX-XXXX (Accessory 1)

Weight	6.00 lb
Light distribution	symmetric, medium beam [M]
Light source	LED-24/42W / 325 mA - 2200-6000K
CRI	80
Power supply	electronic gear
LEDs	24
Rated input power	51 W



**Nominal Lumen (lm)**

LED Lumen	230
Total Lumen	5520
T <sub>j</sub>	85

**Delivered lumens (lm)**

LED Lumen	176.6
Total Lumen	4237.4
T <sub>a</sub>	25

## DAS140 TW LED TUNABLE WHITE

**Specifications****Material description**

Body	Marine-grade, die-cast aluminum alloy
Lens	Safety glass lens
Colors	<div style="display: inline-block; width: 20px; height: 10px; background-color: black; margin-right: 10px;"></div> RAL9004 Black <div style="display: inline-block; width: 20px; height: 10px; background-color: #808080; margin-right: 10px;"></div> RAL9007 Grey Metallic <div style="display: inline-block; width: 20px; height: 10px; background-color: #F0F0F0; margin-right: 10px;"></div> RAL9016 White <div style="display: inline-block; width: 20px; height: 10px; background-color: black; margin-right: 10px;"></div> RAL8019 Dark Bronze
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.658 ft <sup>2</sup>

**Electrical description**

Driver / Ballast	DALI
Power factor	> 0.9

**DAS140 TW LED TUNABLE WHITE****Additional information**

---

Lifetime Ta=25°/40° L90B10 > 90000h


Listings Contact WE-EF USA for ETL/UL certification status.

---

## DAS140 TW LED TUNABLE WHITE

**Optical Accessories****Linear spread lens**


Description	Part ID
IO-180-DAC140-LED	134-2064



## DAS140 TW LED TUNABLE WHITE

## Wallwash lens


Description	Part ID
IO-20-WW-DAC140-LED	134-2065



C1

## Honeycomb louvre

Description	Part ID
IW-DA_140-LED	134-2066



C1