


Description


IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Weight	5.50 kg
Light distribution	symmetric, medium beam [M]
Light source	LED-24/42W / 325 mA -
	2200-6000K
CRI	80
Power supply	EC
LEDs	24
Rated input power	51 W
NI / \	
Nominal Lumen (Im)	
LED Lumen	250
	250 6000
LED Lumen	
LED Lumen Total Lumen	6000
LED Lumen Total Lumen Tj	6000
LED Lumen Total Lumen Tj Rated lumens (lm)	6000 85

DAS140-PM TW LED





Specifications Material description

Body	Marine-grade, all aluminium construction
Lens	Safety glass lens
Colours	RAL9004 Signal black
	RAL9006 White aluminium
	RAL9007 Grey aluminium
	RAL9016 Traffic white
Gasket	Silicone CCG [®] Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE+Primer

Electrical description DALI

Driver / Ballast

Additional information


134-2319

DAS140-PM TW LED

Optical Accessories


Linear spread lens

Description	Part ID
IO-180-DAC140-LED	134-2064



Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	



we-ef

134-2319

DAS140-PM TW LED



Honeycomb louvre

Description	Part ID
IW-DA_140-LED	134-2066



134-2319

DAS140-PM TW LED



Mounting Accessories

Adaptor for side conduit entry

Description	Part ID	А	C1
DA14 Adaptor for DAC140/DAS140-	134-2109	31	195
PM			

