



Description


IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.


Other standardised housing lengths available on request.

Weight	5.50 kg
Light distribution	symmetric, wide beam [B]
Light source	LED-24/42W / 325 mA -
	2200-6000K
CRI	80
Power supply	EC
LEDs	24
Rated input power	51 W
Nominal Lumen (lm)	
LED Lumen	250
Total Lumen	6000
Тј	85
Rated lumens (lm)	
LED Lumen	180.9
Total Lumen	4340.7
Та	25









Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Driver / Ballast DALI

Additional information





Optical Accessories

Linear spread lens

Description	Part ID
IO-180-DAC140-LED	134-2064



Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	





DAS140-PM TW LED

Honeycomb louvre

Description	Part ID	
IW-DA_140-LED	134-2066	







Mounting Accessories

Adaptor for side conduit entry

Description	Part ID	Α	C1
DA14 Adaptor for DAC140/DAS140-	134-2109	31	195
PM			

