



#### **Description**


IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 1.5 - 5 ft., to be specified at time at ordering. Integral driver in thermally separated compartment. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. Tunable White technology. DALI interface. The luminaire is factory-sealed and does not need to be opened during installation.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	5.50 lb
Light distribution	symmetric, wide beam [W]
Light source	LED-24/42W / 325 mA - 2200-6000K
CRI	80
Power supply	electronic gear
LEDs	24
Rated input power	51 W
Nominal Lumen (lm)	
LED Lumen	250
Total Lumen	6000
Tj	85
Delivered lumens (lm)	
LED Lumen	180.9
Total Lumen	4340.7
Та	25





# Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

### **Electrical description**

Driver / Ballast DALI

#### **Additional information**

Listings Contact WE-EF USA for ETL/UL certification status.



# **Optical Accessories**

## **Linear spread lens**

Description	Part ID	
IO-180-DAC140-LED	134-2064	



\_\_\_\_C1\_\_\_



#### Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	



## **Honeycomb louvre**

Description	Part ID	
IW-DA 140-LED	134-2066	





## **Mounting Accessories**

## Adaptor for side conduit entry

Description	Part ID A	C1
DA14 Adaptor for DAC140/DAS140-PM	134-2109 1.20	7.70

