




Description


IP66, Class I. Class II on request. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.

Other standardised housing lengths available on request.

Light distribution symmetric, narrow beam [E] Light source LED-24/42W / 325 mA - 2200-6000K CRI 80 Power supply EC LEDs 24 Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4 Ta 25	Weight	5.50 kg
2200-6000K CRI 80 Power supply EC LEDs 24 Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Light distribution	symmetric, narrow beam [E]
CRI 80 Power supply EC LEDs 24 Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Light source	LED-24/42W / 325 mA -
Power supply EC LEDs 24 Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4		2200-6000K
LEDs 24 Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	CRI	80
Rated input power 51 W Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Power supply	EC
Nominal Lumen (Im) LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	LEDs	24
LED Lumen 250 Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Rated input power	51 W
Total Lumen 6000 Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Nominal Lumen (lm)	
Tj 85 Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	LED Lumen	250
Rated lumens (Im) LED Lumen 199.6 Total Lumen 4789.4	Total Lumen	6000
LED Lumen 199.6 Total Lumen 4789.4	Tj	85
Total Lumen 4789.4	Rated lumens (lm)	
	LED Lumen	199.6
Ta 25	Total Lumen	4789.4
	Та	25







Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

TO NE 7004 Signal Black

RAL9007 Grey aluminium

RAL9006 White aluminium

RAL7016 Anthracite grey

MAL7010 Antinacite gre

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE

Electrical description

Driver / Ballast DALI

Additional information

WE-EF LEUCHTEN GmbH





Optical Accessories

Linear spread lens

Description	Part ID
IO-180-DAC140-LED	134-2064



Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	





DAS140-PM TW LED

Honeycomb louvre

Description	Part ID	
IW-DA_140-LED	134-2066	







Mounting Accessories

Adaptor for side conduit entry

