



#### **Description**


IP66, Class I. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® gasket. Safety glass lens. Two cable entries. Ceiling mount through canopy. Cable suspension 0.5 - 1.5 m. To be specified at time at ordering. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. Factory installed LED circuit board. Tunable White Technology. The luminaire is factory-sealed and does not need to be opened during installation.


Other standardised housing lengths available on request.

Weight	5.50 kg	
Light distribution	symmetric, narrow beam [E]	
Light source	LED-24/42W / 325 mA -	
	2200-6000K	
CRI	80	
Power supply	EC	
LEDs	24	
Rated input power	51 W	
Nominal Lumen (lm)		
LED Lumen	250	
Total Lumen	6000	
Tj	85	
Rated lumens (lm)		
LED Lumen	199.6	
Total Lumen	4789.4	
Та	25	









# **Specifications Material description**

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

#### **Electrical description**

Driver / Ballast DALI

#### **Additional information**





# **Optical Accessories**

## **Linear spread lens**

Description	Part ID
IO-180-DAC140-LED	134-2064



### Wallwash lens

Description	Part ID	
IO-20-WW-DAC140-LED	134-2065	





#### **DAS140-PM TW LED**

# **Honeycomb louvre**

Description	Part ID	
IW-DA_140-LED	134-2066	







# **Mounting Accessories**

# Adaptor for side conduit entry

