

Description

DOC110 LED for new construction. For remodel projects, see DOC110 LED [For Remodel] version.

IP66, Class I. IK07. Marine-grade, die-cast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Separate IP66 driver housing. CAD-optimized optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. 0-10V Dimming comes standard with luminaire.

A pre-installation blockout, proud or flush, is available and recommended for mounting in concrete ceilings; to be ordered separately.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)

Weight	2.86 lb
Light distribution	symmetric, wide beam [W]
Light source	LED-6/12W / 700 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	15 W
Nominal Lumen (lm)	
LED Lumen	246
Total Lumen	1476
Tj	85
Delivered lumens (lm)	
LED Lumen	190.5
Total Lumen	1142.7
Та	25

we-ef

DOC110 LED [New Construction]





Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE



Electrical description

Power supply	Integral 120-277V/0-10V dimming driver
Additional info	rmation
Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.



Optical Accessories

Linear spread lens

Description	Part ID	C1	
IO-180-DOC110-LED	134-1637	3.86	





Wallwash lens

Description	Part ID	C1
IO-20-DOC110-LED	134-1683	3.85

