

105-9944-70


RMT320 LED Two-sided



Description

IP66. Post top LED luminaire. Integrated heat sinks. Easy removal and replacement of LED board. CAD-optimized OLC PMMA lens for multi-layer illumination and superior glare control.

Weight	8.00 lb
Light distribution	[S70] Type II Short
Light source	LED-24/72W / 1050 mA - 3000 K
CRI	70
Power supply	electronic gear
LEDs	24
Rated input power	79 W
Nominal Lumen (lm)	
LED Lumen	490
Total Lumen	11760
Tj	85
Delivered lumens (lm)	
LED Lumen	450.9
Total Lumen	10820.6
Ta	25



Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	RFC® Reflection Free Contour technology
Colors	<div><div></div> RAL9004 Black</div> <div><div></div> RAL9007 Grey Metallic</div> <div><div></div> RAL9016 White</div> <div><div></div> RAL8019 Dark Bronze</div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK09
Corrosion resistance	5CE

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	> 0.9

105-9944-70



RMT320 LED Two-sided

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
----------	----------------------------