ZFS460 LED

we-ef



Description

IP66, Class I, Class II on request. IK07. Marine-grade, diecast aluminum alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. UV-resistant polycarbonate main lens (open at the bottom). Integral driver, thermally separated. CAD-optimized indirect optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board, removable for upgrading. 0-10V Dimming comes standard with luminaire. The luminaire is factory sealed and does not need to be opened during installation.

Optional 2200 K version available, to be specified at time of ordering.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX - 9004 (Black)


+ XXX-XXXX (Accessory 1)


Weight	20.94 lb	
Light distribution	[S65] Type III Medium	
Light source	LED-18/36W / 700 mA - 2700 K	
CRI	80	
Power supply	electronic gear	
LEDs	18	
Rated input power	41 W	
Nominal Lumen (lm)		
LED Lumen	270	
Total Lumen	4860	
Tj	85	
Delivered lumens (Im)		
LED Lumen	244.8	
Total Lumen	4405.6	
Та	25	

115-2003

ZFS460 LED







Specifications

Material description

Body Marine-grade, die-cast aluminium alloy Lens Polycarbonate (open at the bottom)

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE
Windage 0.090 m²

Electrical description

Driver / Ballast	Standard. DALI or 1-10V on request	
Power factor	> 0.9	

WE-EF LIGHTING USA, LLC

115-2003

ZFS460 LED



Additional information

Lifetime Ta=25°/40° L90B10 > 90000h