



Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. UV-resistant polycarbonate main lens (open at the bottom). The luminaire is factory sealed and does not need to be opened during installation. Integral EC converter, thermally separated. Factory installed LED circuit board. Removable LED boards for upgrading. CAD-optimised indirect optics for superior illumination and glare control.

Optional 2200 K version available. To be specified at time of ordering.

Weight 9.50 kg Light distribution asymmetric, side throw [S70] Light source LED-18/54W / 1050 mA - 4000 K CRI 80 Power supply EC LEDs 18 Rated input power 59 W Mominal Lumen (Im) 100 Total Lumen 8100 Tj 85 Rated lumens (Im) 198.9 LED Lumen 398.9 Total Lumen 7180.2 Ta 25		
Light source LED-18/54W / 1050 mA - 4000 K CRI 80 Power supply EC LEDs 18 Rated input power 59 W Nominal Lumen (Im) 1 LED Lumen 450 Total Lumen 8100 Tj 85 Rated lumens (Im) 1 LED Lumen 398.9 Total Lumen 7180.2	Weight	9.50 kg
CRI80Power supplyECLEDs18Rated input power59 WNominal Lumen (Im)450LED Lumen8100Total Lumen (Im)85Rated lumens (Im)398.9LED Lumen398.9	Light distribution	asymmetric, side throw [S70]
Power supplyECLEDs18Rated input power59 WNominal Lumen (Im)LED Lumen450Total Lumen8100Tj85Rated lumens (Im)LED Lumen398.9Total Lumen7180.2	Light source	LED-18/54W / 1050 mA - 4000 K
LEDs18Rated input power59 WNominal Lumen (Im)LED Lumen450Total Lumen8100Tj85Rated lumens (Im)LED Lumen398.9Total Lumen7180.2	CRI	80
Rated input power59 WNominal Lumen (Im)LED Lumen450Total Lumen8100Tj85Rated lumens (Im)LED Lumen398.9Total Lumen7180.2	Power supply	EC
Nominal Lumen (Im)LED Lumen450Total Lumen8100Tj85Rated lumens (Im)LED Lumen398.9Total Lumen7180.2	LEDs	18
LED Lumen 450 Total Lumen 8100 Tj 85 Rated lumens (lm) 100 LED Lumen 398.9 Total Lumen 7180.2	Rated input power	59 W
Total Lumen8100Tj85Rated lumens (lm)398.9LED Lumen7180.2	Nominal Lumen (lm)	
Tj85Rated lumens (lm)398.9LED Lumen7180.2	LED Lumen	450
Rated lumens (Im)LED Lumen398.9Total Lumen7180.2	Total Lumen	8100
LED Lumen 398.9 Total Lumen 7180.2	Тј	85
Total Lumen 7180.2	Rated lumens (lm)	
	LED Lumen	398.9
Ta 25	Total Lumen	7180.2
	Та	25





Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Polycarbonate (open at the bottom)
Colours	RAL9004 Signal black
	RAL9006 White aluminium
	RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Windage	0.090 m ²

Electrical description

Driver / Ballast	Standard. DALI or 1-10V on request
Power factor	> 0.9

Additional information

Lifetime

Ta=40° L90B10 > 90000h

115-2014

ZFS460 LED

Control

Eco Step Dim[®] Basic

Description	Part ID
Eco Step Dim [®] Basic LED	430-0001

Eco Step Dim[®] Advanced

Description	Part ID
Eco Step Dim [®] Advanced LED	430-0002

R2C Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019