

DAC110 LED




#### Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG<sup>®</sup> gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC<sup>®</sup> One LED Concept. Factory installed LED circuit board.


Other standardised housing lengths, 250 mm and 300 mm available on request.


Optional 2200 K version available. To be specified at time of ordering.

Weight	2.00 kg	
Light distribution	wallwash [A20]	
Light source	LED-6/12W / 700 mA - 2700 K	
CRI	80	
Power supply	EC	
LEDs	6	
Rated input power	14.5 W	
Nominal Lumen (lm)		
LED Lumen	270	
Total Lumen	1620	
Tj	85	
Rated lumens (Im)		
LED Lumen	136.2	
Total Lumen	817.3	
Та	25	



#### DAC110 LED





## Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	RAL9004 Signal black RAL9006 White aluminium RAL9007 Grey aluminium
Gasket	Silicone CCG <sup>®</sup> Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Electrical description	
Driver / Ballast	Integral EC electronic converter in thermally separated compartment

# Power factor >0.9

### Additional information

Lifetime Ta=40° L90B10 > 90000h	
---------------------------------	--


134-2080+134-2361

DAC110 LED

## **Optical Accessories**


#### Linear spread lens

Description	Part ID
IO-180-DAC110	134-2104




### Honeycomb louvre

Description	Part ID
IW-DAC110	134-2105



we-ef



#### DAC110 LED



#### Wallwash lens



### 134-2080+134-2361

DAC110 LED



# **Mounting Accessories**

## Adaptor for side conduit entry

