

DAC110 LED




Description

IP66, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG[®] gasket. Safety glass lens. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC[®] One LED Concept. Factory installed LED circuit board.


Other standardised housing lengths, 250 mm and 300 mm available on request.


Optional 2200 K version available. To be specified at time of ordering.

Weight	2.00 kg
Light distribution	wallwash [A20]
Light source	LED-6/12W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	14.5 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	1860
Тј	85
Rated lumens (lm)	
LED Lumen	156.4
Total Lumen	938.4
Та	25



DAC110 LED





Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colours	RAL9004 Signal black
	RAL9006 White aluminium
	RAL9007 Grey aluminium
Gasket	Silicone CCG [®] Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK07
Corrosion resistance	5CE
Electrical descripti	on
Driver / Ballast	Integral EC electronic converter in thermally separated compartment

Power factor >0.9

Additional information

Lifetime Ta=40° L90B10 > 90000h


134-2082+134-2361

DAC110 LED

Optical Accessories


Linear spread lens

Description	Part ID
IO-180-DAC110	134-2104




Honeycomb louvre

Description	Part ID
IW-DAC110	134-2105



we-ef



DAC110 LED



Wallwash lens



134-2082+134-2361

DAC110 LED



Mounting Accessories

Adaptor for side conduit entry

Description	Part ID	А	C1
DA11 Adaptor for DAC110/DAS110-	134-2107	31	105
PM			

