



#### **Description**


IP66, Class I. IK09. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gaskets. Polycarbonate main lens. CAD-optimised indirect optics for superior illumination and glare control.


Service door with fused cable connecting box.

Weight	25.00 kg
Light distribution	symmetric distribution [C60]
Light source	LED-FT-24W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	1
Rated input power	27 W
Rated lumens (lm)	
LED Lumen	2968.4
Total Lumen	2968.4
Та	25
Nominal Lumen (lm)	
LED Lumen	4400
Total Lumen	4400
Tc	25









18— 👸 🗆 ø 244-293 🛮 ø 365

# **Specifications Material description**

Body Marine-grade, all-aluminium construction

Lens Polycarbonate lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66

Corrosion resistance 5CE+Primer

### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

#### Additional information

Lifetime Ta=40° L70B50 > 90000h

Warranty Places refer to the LED Warranty

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement

located on www.we-ef.com for further details.

#### **WE-EF LIGHTING Pty Ltd**






# **Mounting Accessories**

### **Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	T1	T2	Weight (kg)
Planted root ESV6 for fixing dimension ø 244-293	300-0457-AP	305	270	106	140	606	506	16	200	50 x 100	18.10



115-9449





## **Optical Accessories**

### **Light shield**

Description	Part ID
LS180-[C60]	159-0321