


#### **Description**


Profile Projector [ZP] for zoom spot. Spherical and aspherical, double flat convex lens system.

IP66, Class III. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. Electronic control gear in separate gear box (constant current), prewired. Gearbox to be ordered separately. One factory installed flange plug M8 x 1.5. Cable length 10 ft. CAD-optimised optics for superior illumination and glare control. Factory-installed LED circuit board.

Weight	1.87 lb
Light distribution	symmetric Zoom-Projector [ZP] - min aperture angle
Light source	LED-1/6W / 500 mA - 4000 K
CRI	80
Power supply	electronic gear
LEDs	1
Rated input power	7.5 W
Delivered lumens (lm)	
LED Lumen	424
Total Lumen	424
Та	25
Nominal Lumen (lm)	
LED Lumen	720
Total Lumen	720
Тс	25







# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

RAL8019 Dark Bronze

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK07
Corrosion resistance 5CE
Windage 0.11 ft²

### **Electrical description**

Driver / Ballast	DALI
Power factor	> 0.9

## 139-2748\_min



### **FLC201 LED ZOOM SPOT PROJECTOR**

### **Additional information**


Lifetime  $Ta=25^{\circ}/40^{\circ} L90B10 > 90000h$ 



# **Mounting Accessories**

### **Ground spike EF**


Description	Part ID	H1	Weight (lb)
EF1-M18 Ground spike	310-0045	10.70	0.80





### **Junction box**

Description	Part ID	А	В	C1	C2
JB200 R82 Junction box	139-2590	2.17	3.23	5.51	3.15





### **Electrical Accessories**

### **Gear box**

Description	Part ID	А	В	C1	C2
FLC201 Remote Gear Box	139-6977	3	4.7	9	7.9

