ETC320-FS LED





Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD-optimised optics for superior illumination and glare control.

Luminaire requires installation blockout and sealable junction box, which are included in supply.

2700 K option available on request.


ASC Anti Slip Coating on request.


IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	3.50 kg
Light distribution	symmetric, medium beam [M]
Light source	LED-6/12W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	15 W
Nominal Lumen (lm)	
LED Lumen	233
Total Lumen	1398
Tj	85
Rated lumens (lm)	
LED Lumen	205
Total Lumen	1230.2
Та	25

ETC320-FS LED







Specifications Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.

ETC320-FS LED



Mounting Accessories

Installation cover

Description	Part ID	C1	
Installation cover BE	185-0796	160	



ETC320-FS LED



Optical Accessories

Colour filter

Description	Part ID	
Colour filter IF	on request	



Surface wash lens

escription P.	C1
ood lens IO-360	96



ETC320-FS LED



Linear spread lens

Description	Part ID	C1
IO-180-ETC/EVC_20-FS-LED	146-0418	110



Wallwash lens

Description	Part ID	C1	
IO-20-WW-ETC/EVC_20-FS-LED	185-7029	110	



ETC320-FS LED



Honeycomb louvre

Description	Part ID	C1
IW-E_C120/320-FS LED	146-0625	110

