



Description

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. LED module can be easily removed for upgrading. CAD-optimised optics for superior illumination and glare control.

Luminaire requires installation blockout and sealable junction box, which are included in supply.


2700 K option available on request.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch here.

Weight	3.50 kg
Light distribution	wallwash
Light source	LED-6/12W / 700 mA - 2700 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	15 W
Nominal Lumen (lm)	
LED Lumen	233
Total Lumen	1398
Tj	85
Rated lumens (lm)	
LED Lumen	158
Total Lumen	947.8
Та	25







Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

Electrical description


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.






Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0796	160







Optical Accessories


Colour filter

Description	Part ID
Colour filter IF	on request



Surface wash lens

Description	Part ID	C1
Flood lens IO-360	146-0419	96





ETC320-FS LED


Linear spread lens

Description	Part ID	C1			
IO-180-ETC/EVC_20-FS-LED	146-0418	110	_	_	



Wallwash lens

Description	Part ID C1
20-WW-ETC/EVC_20-FS-LED	185-7029 1



185-7272+185-7029



ETC320-FS LED

Honeycomb louvre

Description	Part ID	C1		
IW-E_C120/320-FS LED	146-0625	110		

