



Description

RGBW Colour Changer. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Factory-sealed termination chamber complete with cable gland and 0.5 m of flexible PVC free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with WE-EF Colour Boost Technology. DMX Interface. For other control interface options to suit specific project requirements, contact WE-EF.


Luminaire installation blockout and sealable junction box included in supply.

Weight	11.00 kg	
Light distribution	symmetric, wallgrazer [A6]	
Light source	LED-48/30W - RGBW	
CRI	20/80	
Power supply	EC	
LEDs	24	
Rated input power	32 W	
Nominal Lumen (lm)		
LED Lumen	140	
Total Lumen	3360	
Tj	85	
Rated lumens (lm)		
LED Lumen	92.6	
Total Lumen	2223.3	
Та	25	

1 of 7







Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS hardware

Ingress protection IP69
Impact resistance IK10+

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter with DMX Interface

Termination Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300



WE-EF LIGHTING (Thailand) Co., Ltd.






Optical Accessories

Flood lens

Description	Part ID	C1
Flood lens IO-360	185-7579	220



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220






ETC340-FS CC LED

Wallwash lens

Description	Part ID	C1
Wallwash lens 10-20	185-7589	220





ETC340-FS CC LED

Control

DMX Wireless Antenna

Description	Part ID
Antenna RF1.8dB	430-0018

DMX Wireless Repeater

Description	Part ID	
DMX Wireless Repeater	400-0477	





ETC340-FS CC LED

DMX Wireless Transceiver

Description	Part ID
DMX Wireless Transceiver	400-0476

