



Description

Tunable white. IP69. IK10+. Stainless steel construction including PCS hardware. Safety glass lens; max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. LED circuit board with Tunable White Technology. DALI Interface. For other control interface options to suit specific project requirements, contact WE-EF.


Luminaire installation blockout and sealable junction box included in supply.

Weight	11.00 kg
Light distribution	symmetric, wallgrazer [A6]
Light source	LED-24/30W / 225 mA -
	2200-6000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	32 W
Nominal Lumen (lm)	
LED Lumen	178.3
Total Lumen	2140
Tj	85
Rated lumens (lm)	
LED Lumen	120.5
Total Lumen	1445.5
Та	25









Specifications

Material description

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS hardware

Ingress protection IP69
Impact resistance IK10+

Electrical description

Driver / Ballast Integral EC electronic converter with DALI Interface

Additional information





Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0326	300







Optical Accessories

Flood lens

Description	Part ID	C1
Flood lens IO-360	185-7579	220



Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	185-7580	220






EVC340-FS TW LED

Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	185-7589	220



WE-EF LIGHTING (Thailand) Co., Ltd.