we-ef

FLC321 Space frame



Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

12W, 18W, 26W / 120-277V / 0-10V Dimming.


Including terminal box, for mounting on Ø 1.89-2.36 in pipes or space frames.


Optical accessories are factory-installed. To be specified at time of ordering.

Weight	8.00 lb
Light distribution	symmetric, very narrow beam, 'sharp cut-off' [VNS]
Light source	LED-6/12W / 700 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	14.5 W
Nominal Lumen (lm)	
LED Lumen	290
Total Lumen	1740
Тј	85
Delivered lumens (lm)	
LED Lumen	225.5
Total Lumen	1353
Та	25

we-ef

FLC321 Space frame





Specifications Material description

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE
Windage 0.7 ft²

Electrical description

Driver / Ballast 120-277V AC/50-60 Hz

Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

WE-EF LIGHTING USA, LLC

we-ef

FLC321 Space frame

Control

0-10 V, 24VDC low voltage version

Description	Part ID
24VDC low voltage version, 0-10 V	0033



FLC321 Space frame

Optical Accessories

Softening Lens

Description	Part ID	C1
Flood lens IO-360	145-9992	3.43



WE-EF LIGHTING USA, LLC



FLC321 Space frame

Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	145-9991	3.43



Wallwash lens

escription Part ID	C1
Vallwash lens IO-20 145-99	3.43




—С1—

we-ef

FLC321 Space frame


Honeycomb louvre

Description	Part ID	C1		
Honeycomb louvre IW	145-9994	3.43		



Glare shield

Descri	CHUUH	Part ID A		C1
Glare	re shield ES	145-9995 2.1	17	4.49



we-ef

FLC321 Space frame

Snoot

Description	Part ID	Α	C1
Snoot ET	145-9996	2.20	4.49

