### we-ef

#### **FLC321 Space frame**



#### **Description**

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

12W, 18W, 26W / 120-277V / 0-10V Dimming.


Including terminal box, for mounting on Ø 1.89-2.36 in pipes or space frames.


Optical accessories are factory-installed. To be specified at time of ordering.

Weight	8.00 lb
Light distribution	symmetric, very narrow beam, 'sharp cut-off' [VNS]
Light source	LED-6/18W / 1050 mA - 2700 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	21 W
Nominal Lumen (lm)	
LED Lumen	375
Total Lumen	2250
Tj	85
Delivered lumens (lm)	
LED Lumen	291.6
Total Lumen	1749.6
Та	25

## we-ef

#### **FLC321 Space frame**





# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens Safety glass lens

Colors RAL9004 Black

RAL9007 Grey Metallic

RAL9016 White

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE
Windage 0.7 ft²

#### **Electrical description**

Driver / Ballast 120-277V AC/50-60 Hz

#### **Additional information**

Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

#### **WE-EF LIGHTING USA, LLC**

# we-ef

### **FLC321 Space frame**

#### **Control**

### 0-10 V, 24VDC low voltage version

Description	Part ID
24VDC low voltage version, 0-10 V	0033

# we-ef

### **FLC321 Space frame**

### **Optical Accessories**

#### **Softening Lens**

Description	Part ID	C1
Flood lens 10-360	145-9992	3.43



**WE-EF LIGHTING USA, LLC** 

# we-ef

#### **FLC321 Space frame**

### **Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	145-9991	3.43



#### Wallwash lens

escription Part ID	C1
Vallwash lens IO-20 145-99	3.43




#### **WE-EF LIGHTING USA, LLC**

# we-ef

### **FLC321 Space frame**


### Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	145-9994	3.43



#### Glare shield

escription Part ID A C1
are shield ES 145-9995 2.17 4.49



# we-ef

### **FLC321 Space frame**

#### **Snoot**

Description	Part ID	Α	C1
Snoot ET	145-9996	2.20	4.49

