

#### Description

IP66. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG<sup>®</sup> Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control.

12W, 18W, 26W / 120-277V / 0-10V Dimming.


Including terminal box, for mounting on ø 1.89-2.36 in pipes or space frames.


Optical accessories are factory-installed. To be specified at time of ordering.

Weight	8.00 lb
Light distribution	symmetric, very narrow beam, 'sharp cut-off' [VNS]
Light source	LED-6/18W / 1050 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	6
Rated input power	21 W
Nominal Lumen (lm)	
LED Lumen	405
Total Lumen	2430
Tj	85
Delivered lumens (lm)	
LED Lumen	314.9
Total Lumen	1889.5
Та	25

#### WE-EF LIGHTING USA, LLC

### FLC321 Space frame





#### Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Safety glass lens
Colors	RAL9004 BlackRAL9007 Grey MetallicRAL9016 White
Gasket	Silicone CCG <sup>®</sup> Controlled Compression Gasket
Fasteners	PCS hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE
Windage	0.7 ft <sup>2</sup>

### **Electrical description**

Driver / Ballast	120-277V AC/50-60 Hz
Additional infor	mation
Lifetime	Ta=25°/40° L90B10 > 90000h
Listings	ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.

FLC321 Space frame

# we-ef

## Control

### 0-10 V, 24VDC low voltage version

Description	Part ID
24VDC low voltage version, 0-10 V	0033


FLC321 Space frame

# we-ef

## **Optical Accessories**

#### **Softening Lens**


Description	Part ID	C1
Flood lens IO-360	145-9992	3.43



#### FLC321 Space frame


#### Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	145-9991	3.43



#### Wallwash lens


escription	C1
allwash lens 10-20	3 3.43




#### FLC321 Space frame

#### Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	145-9994	3.43



#### Glare shield



#### WE-EF LIGHTING USA, LLC

## FLC321 Space frame

# we-ef

#### Snoot

Description	Part ID	А	C1
Snoot ET	145-9996	2.20	4.49

