

FLC321 Wall bracket



Description

IP66. IK08. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two cable entries.

Mains voltage versions: DALI interface Class I.
24VDC low voltage versions: ON-OFF Class III.



Knuckle permits 340° rotation, forward tilt 54° and backward tilt 90°.
Remote 24VDC power supply to be ordered separately.
Optical accessories are factory-installed. To be specified at time of ordering.

Weight	4.30 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-6/26W / 1400 mA - 3000K
CRI	80
Power supply	EC
LEDs	6
Rated input power	27 W

Nominal Lumen (lm)	
LED Lumen	550
Total Lumen	3300
Tj	85

Rated lumens (lm)	
LED Lumen	408.9
Total Lumen	2453.5
Ta	25

FLC321 Wall bracket



Specifications
Material description

Table with 2 columns: Component and Description. Rows include Body (Marine-grade, all aluminium construction), Lens (Safety glass lens), Colours (RAL9004 Signal black, RAL9006 White aluminium, RAL9007 Grey aluminium), Gasket (Silicone CCG® Controlled Compression Gasket), Fasteners (PCS hardware), Ingress protection (IP66), Impact resistance (IK08), and Corrosion resistance (5CE).

Electrical description

Table with 2 columns: Component and Description. Row includes Driver / Ballast (DALI).

Additional information

Table with 2 columns: Component and Description. Row includes Lifetime (Ta=40° L90B10 > 90000h).

Control**1-10 V analogue dimming interface**

Description	Part ID	C
1-10 V analogue dimming interface	430-0011	90

DALI interface

Description	Part ID
Low voltage DALI interface	0026


0-10 V, 24VDC low voltage version

Description	Part ID
24VDC low voltage version, 0-10 V	0033

Optical Accessories


Surface wash lens

Description	Part ID	C1
Flood lens IO-360	145-9992	87



Linear spread lens


Description	Part ID	C1
Linear spread lens IO-180	145-9991	87



FLC321 Wall bracket


Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	145-9993	87



Honeycomb louvre


Description	Part ID	C1
Honeycomb louvre IW	145-9994	87



FLC321 Wall bracket

Glare shield

Description	Part ID	A	C1
Glare shield ES	145-9995	55	114



Snoot

Description	Part ID	A	C1
Snoot ET	145-9996	56	114

