FLC311 Wall bracket





Description

IP66. IK08. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two cable entries.

Mains voltage versions: DALI interface Class I.

24VDC low voltage versions: ON-OFF Class III.


Knuckle permits 340° rotation, forward tilt 54° and backward tilt 90°.


Remote 24VDC power supply to be ordered separately.

Weight	3.20 kg			
Light distribution	symmetric, medium beam [M]			
Light source	LED-3/9W / 250 mA - 3000 K			
CRI	80			
Power supply	EC			
LEDs	3			
Rated input power	11 W			
Nominal Lumen (lm)				
LED Lumen	365			
Total Lumen	1095			
Tj	85			
Rated lumens (lm)				
LED Lumen	281			
Total Lumen	842.9			
Та	25			

FLC311 Wall bracket







Specifications Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE

Windage 0.065 m²

Electrical description

Driver / Ballast DALI

Additional information

Lifetime Ta=40° L90B10 > 90000h

FLC311 Wall bracket



Control

1-10 V analogue dimming interface

Description	Part ID	С
1-10 V analogue dimming interface	430-0011	90

DALI interface

Description	Part ID	
Low voltage DALI interface	0026	

0-10 V, 24VDC low voltage version

Description	Part ID
24VDC low voltage version, 0-10 V	0033

FLC311 Wall bracket




Optical Accessories

Surface wash lens

Description	Part ID	C1	
Flood lens IO-360 for [EE]	145-7786	59	

59



Flood lens IO-360 for [EES] 145-7780





we-ef

Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	145-7781	59



Wallwash lens

Description	C1
Wallwash lens IO-20	59









Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	145-7783	59



Glare shield

escription () A (C1
ilare shield ES		8!





FLC311 Wall bracket

Snoot

Description	Part ID	Α	C1
Snoot ET	145-7785	34	85

