

FLC311 Wall bracket

**Description**

IP66. IK08. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two cable entries.



Mains voltage versions, ON-OFF Class I. 1-10 V analogue dimming or DALI interface available on request; refer to accessory listings.

Knuckle permits 340° rotation, forward tilt 54° and backward tilt 90°.

Optical accessories are factory-installed. To be specified at time of ordering.

Weight	3.20 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-3/12W / 350 mA - 2700 K
CRI	80
Power supply	EC
LEDs	3
Rated input power	13.9 W
Nominal Lumen (lm)	
LED Lumen	455
Total Lumen	1365
T _j	85
Rated lumens (lm)	
LED Lumen	383.1
Total Lumen	1149.4
T _a	25

FLC311 Wall bracket



Specifications

Material description

Body Marine-grade, all aluminium construction

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS hardware

Ingress protection IP66

Impact resistance IK08

Corrosion resistance 5CE

Windage 0.065 m²

Electrical description

Driver / Ballast DALI

Additional information

Lifetime Ta=25° L90B10 > 90000h


Energy efficiency class D-E (Light source)

FLC311 Wall bracket

Optical Accessories


Flood lens

Description	Part ID	C1
I0-360-FLC311 for [EE]	145-7786	59



C1

I0-360-FLC311 for [EES] 145-7780 59




C1

FLC311 Wall bracket


Linear spread lens

Description	Part ID	C1
IO-180-FLC311	145-7781	59



Wallwash lens


Description	Part ID	C1
IO-20-FLC311	145-7782	59



FLC311 Wall bracket


Honeycomb louvre

Description	Part ID	C1
IW-FLC311	145-7783	59



Glare shield


Description	Part ID	A	C1
ES-FLC311	145-7784	34	85



FLC311 Wall bracket

Snoot

Description	Part ID	A	C1
ET-FLC311	145-7785	34	85



FLC311 Wall bracket

Control**0-10 V, 24VDC low voltage version**

Description	Part ID
24VDC low voltage version, 0-10 V	0033