

## FLC301 Wall bracket

**Description**

IP66. IK07. Marine-grade, all aluminium construction. 5CE superior corrosion protection including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. Two cable entries.

Mains voltage versions, ON-OFF Class I. Integral EC electronic converter.

24VDC low voltage versions available upon request, ON-OFF Class III.

Knuckle permits 340° rotation, forward tilt 73° and backward tilt 90°.

Remote 24VDC power supply to be ordered separately.

|                    |                                      |
|--------------------|--------------------------------------|
| Weight             | 2.30 lb                              |
| Light distribution | linear spread, very narrow beam [VN] |
| Light source       | LED-1/4W / 350 mA - 2700 K           |
| CRI                | 80                                   |
| Power supply       | electronic gear                      |
| LEDs               | 1                                    |
| Rated input power  | 5 W                                  |



**Nominal Lumen (lm)**

|             |     |
|-------------|-----|
| LED Lumen   | 490 |
| Total Lumen | 490 |
| Tj          | 85  |

**Delivered lumens (lm)**

|             |       |
|-------------|-------|
| LED Lumen   | 384.6 |
| Total Lumen | 384.7 |
| Ta          | 25    |

**FLC301 Wall bracket**



**Specifications**

**Material description**

|                      |  |
|----------------------|--|
| Body                 | Marine-grade, all aluminium construction   |
| Lens                 | Safety glass lens  |
| Colors               | <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 15px; background-color: black; margin-right: 5px;"></div> <span>RAL9004 Black</span> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: grey; margin-right: 5px;"></div> <span>RAL9007 Grey Metallic</span> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 15px; background-color: white; border: 1px solid black; margin-right: 5px;"></div> <span>RAL9016 White</span> </div> |
| Gasket               | Silicone CCG® Controlled Compression Gasket  |
| Fasteners            | PCS hardware   |
| Ingress protection   | IP66   |
| Impact resistance    | IK07   |
| Corrosion resistance | 5CE  |
| Windage              | 0.54 ft <sup>2</sup>   |

**Electrical description**

|                  |  |
|------------------|--|
| Power supply     | 120V AC/50-60 Hz (24V DC available upon request) |
| Driver / Ballast | Integral EC electronic converter                 |

**Additional information**

|          |  |
|----------|--|
| Lifetime | Ta=25°/40° L90B10 > 90000h                                 |
| Listings | ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations. |

**FLC301 Wall bracket**

---


**Optical Accessories**

**Linear spread lens**

---

| Description               | Part ID  | C1   |
|---------------------------|----------|------|
| Linear spread lens IO-180 | 145-7229 | 42.5 |

---




**FLC301 Wall bracket**

---

**Wallwash lens**


| Description         | Part ID  | C1   |
|---------------------|----------|------|
| Wallwash lens IO-20 | 145-7230 | 42.5 |



---

**Honeycomb louvre**


| Description         | Part ID  | C1   |
|---------------------|----------|------|
| Honeycomb louvre IW | 145-7231 | 42.5 |



**FLC301 Wall bracket**


**Glare shield**

| Description     | Part ID  | A    | C1 |
|-----------------|----------|------|----|
| Glare shield ES | 145-7232 | 20.5 | 58 |



**Snoot**

| Description | Part ID  | A    | C1 |
|-------------|----------|------|----|
| Snoot ET    | 145-7233 | 22.5 | 58 |



**FLC301 Wall bracket**

---

**Control**

**DALI interface**

---

| Description                | Part ID |
|----------------------------|---------|
| Low voltage DALI interface | 0026    |

---

**ON-OFF, 24VDC low voltage version**

---

| Description               | Part ID |
|---------------------------|---------|
| 24VDC low voltage version | 0025    |

---