

## CFY259 LED II Security Bollard

**Description**

Impact-Rated Bollard. IP66. Class I. IK10. Marine-grade, all aluminum construction. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. Diffused safety glass lens. CAD-optimized indirect optics for superior illumination and glare control. Integral driver in thermally separated compartment. Factory-installed LED circuit board.

Crash rated for small vehicles travelling up to 40mph (SC40), pick-up vehicles travelling up to 40mph (PU40), and medium-duty vehicles travelling up to 30mph (M30).

Pre-wired post complete with cable connecting box and fuse for mains connection.

Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.

Example: XXX-XXXX-9004 (Black)  
+ XXX-XXXX (Accessory 1)


Weight	39.68 lb
Light distribution	asymmetric, forward-throw, two-sided
Light source	LED-2x6/36W / 1050 mA - 4000 K
CRI	80
Power supply	M30
LEDs	12
Rated input power	41 W

**Nominal Lumen (lm)**

LED Lumen	450
Total Lumen	5400
T <sub>j</sub>	85

**Delivered lumens (lm)**

LED Lumen	95.3
Total Lumen	1143.1
T <sub>a</sub>	25

**CFY259 LED II Security Bollard****Specifications****Material description**

Body	Marine-grade, all-aluminium construction
Lens	Diffused glass
Colors	<div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: black;"></span> </div> <div>RAL9004 Black</div> <div style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: #808080;"></span> </div> <div>RAL9007 Grey Metallic</div> <div style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: #F0F0F0;"></span> </div> <div>RAL9016 White</div> <div style="text-align: center;"> <span style="display: inline-block; width: 15px; height: 15px; background-color: black;"></span> </div> <div>RAL8019 Dark Bronze</div> </div>
Gasket	Silicone CCG® Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE

**Electrical description**

Power supply	Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.
Driver / Ballast	Integral EC electronic converter

**CFY259 LED II Security Bollard****Additional information**

---

Lifetime	Ta=25°/40° L90B10 > 90000h
----------	----------------------------

---

**CFY259 LED II Security Bollard****Mounting Accessories****Planted root**

Description	Part ID	D1	D2	D3	D4	H1	H2	M1	M2	Weight(lb)
Planted root ESV4	300-0464	8.66	7.48	4.25	4.02	15.75	13.78	.35	.24	9.48

