

# CFT540-CC LED




#### **Description**


RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CADoptimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Weight	13.30 kg	
Light distribution	rectangular [R]	
Light source	LED-36/95W - RGBW/4K	
CRI	20/80	
Power supply	ECG [DMX]	
LEDs	36	
Rated input power	99 W	
Nominal Lumen (lm)		
LED Lumen	275	
Total Lumen	9900	
Tj	85	
Rated lumens (lm)		
LED Lumen	212.9	
Total Lumen	7664.6	
Та	25	

#### CFT540-CC LED







# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy

Lens PMMA RFC® Reflection Free Contour technology

Colours RAL9004 Signal black

RAL9006 White aluminium

RAL9007 Grey aluminium

RAL7016 Anthracite grey

RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK08
Corrosion resistance 5CE
Windage 0.24 m²

#### **Electrical description**

Power supply 220-240V / 50-60 Hz

Driver / Ballast Integral EC electronic converter. DMX

Power factor > 0.9

Surge protection 6/6 kV (optional SP10)

#### **Fagerhult Lighting Ltd**

#### CFT540-CC LED



#### **Additional information**

Lifetime  $Ta=25^{\circ} L90B10 > 90000h$ 

ENERGY EFFICIENCY C-D (Light source)

**CLASS** 

#### CFT540-CC LED



# **Electrical Accessories**

#### **DMX Luminaire**

Description	Part ID
DMX Communication IN&OUT +	430-0012
Power Supply Cable	

#### CFT540-CC LED



#### **Control**

#### **DMX Wireless Antenna**

Description	Part ID	
Antenna RF 5dB	430-0036	
Antenna RF1.8dB	430-0018	