

#### Description

RGBW/RGBA Colour Changer. IP66. Class I. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG<sup>®</sup> Controlled Compression Gasket. RFC<sup>®</sup> Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DMX interface. CADoptimised optics for superior illumination and glare control. OLC<sup>®</sup> One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.

Weight	13.30 kg
Light distribution	rectangular [R]
Light source	LED-36/95W/230mA - RGBA (PCA)
CRI	20
Power supply	ECG [DMX]
LEDs	36
Rated input power	99 W
Nominal Lumen (lm)	
LED Lumen	245
LED Lumen Total Lumen	245 8820
Total Lumen	8820
Total Lumen Tj	8820
Total Lumen Tj <b>Rated lumens (lm)</b>	8820 85





# Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	PMMA RFC <sup>®</sup> Reflection Free Contour technology
Colours	RAL9004 Signal black
	RAL9006 White aluminium
	RAL9007 Grey aluminium
Gasket	Silicone CCG <sup>®</sup> Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE+Primer
Windage	0.24 m <sup>2</sup>

# **Electrical description**

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DMX
Power factor	> 0.9
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.

### **Additional information**

Lifetime

Ta=25° L90B10 > 90000h

#### WE-EF LIGHTING Pty Ltd

47 Tarnard Drive, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499 info.australia@we-ef.com - https://we-ef.com/aus Subject to technical changes and errors. - Generated on 14/08/2025

we-ef

## Control

## **DMX Wireless Antenna**

Description	Part ID
Antenna RF 5dB	430-0036
Antenna RF1.8dB	430-0018