



Description

LED upgrade kit to repair or upgrade installed RFL530-SE LED luminaires (from 2014) with [S60] [S65] [S70] [S65] light distribution.

Upgrade kit uses the latest technology for improved energy performance. Connectivity and controls dependent on previous luminaire settings; DALI and 0-10V only possible if luminaire installed with 5-wire cable. One LED retrofit kit possible per luminaire.

Upgrade Kit comes complete with driver, LED board, optics and cables. Quick installation possible with few tools. Installation only possible with 6 LED board and only for forward orientation. No rotation of lenses possible. Not available for existing hybrid installations. A backlight shield cannot be used.

Please specify wattage, colour temperature and light distribution when ordering!

For photometric data see current RFL530-SE LED luminaires

|                    |                                |
|--------------------|--------------------------------|
| Weight             | 1.20 kg                        |
| Light distribution | [S60] [S65] [S70] or [R65]     |
| Light source       | Chassis Kit LED-12/12W / 350mA |
| CRI                | 70/80                          |

**111-1254**


**RFL530-SE LED Upgrade Kit**

**we-ef**



## Specifications

### Material description

|                      |   |
|----------------------|---|
| Body                 | Chassis made of coated steel  |
| Lens                 | NA  |
| Colours              |  RAL9006 White aluminium |
| Gasket               | NA  |
| Fasteners            | Polycarbonate holder  |
| Corrosion resistance | 5CE +Primer   |

### Electrical description

|                  |  |
|------------------|--|
| Power supply     | 220-240V / 50-60 Hz                    |
| Driver / Ballast | Integral EC electronic converter. DALI |
| Power factor     | > 0.9                                  |

### Additional information

|                         |                        |
|-------------------------|------------------------|
| Lifetime                | Ta=25° L90B10 > 90000h |
| Energy efficiency class | C-D (Light source)     |

**WE-EF LEUCHTEN GmbH**

Töpinger Straße 16, 29646 Bispingen, Germany - Phone: +49 5194 909-0  
info@we-ef.com - <https://we-ef.com>

Subject to technical changes and errors. - Generated on 06/09/2025