



Description


IP66, Class I. IK10. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gaskets. Non-reflecting safety glass lens. LED modules can be easily removed for updating. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. DALI.

Recommended mounting height 3,0-4,5 m, depending on lamp type selected. Brackets to be ordered separately. Optional 2200 K version available. To be specified at time of ordering.

Weight	15.30 kg
Light distribution	asymmetric, forward throw [A60]
Light source	LED-24/48W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	24
Rated input power	54 W

Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	7440
Tj	85

Rated lumens (lm)	
LED Lumen	255
Total Lumen	6120
Ta	25



Specifications

Material description

Body	Marine-grade die-cast aluminium alloy
Colours	RAL9004 Signal black RAL9006 White aluminium RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Ingress protection	IP66
Impact resistance	IK10
Corrosion resistance	5CE+Primer

Electrical description

Driver / Ballast	Integral EC electronic converter. DALI
Power factor	< 0.9
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.


Additional information

Lifetime	
----------	--


Mounting Accessories

Wall and pole brackets BA

Description	Part ID	C1	D × L1	H1	Weight (kg)	C	H
BA1-600 Pole bracket, single	300-8001	580	76 x 80	1000	4.50		




BA2-600 Pole bracket, double	300-8002	675	76 x 80	1000	8.50		
------------------------------	----------	-----	---------	------	------	--	--




ASP530 LED

Description	Part ID	C1	D × L1	H1	Weight (kg)	C	H
BA0-420 Wall bracket, single	300-9162	460		100	1000	460	1000




BA1-420 Pole bracket, single	300-9163	420	76 x 80	1000	4	420	1000
------------------------------	----------	-----	---------	------	---	-----	------




ASP530 LED

Description	Part ID	C1	D × L1	H1	Weight (kg)	C	H
BA2-420 Pole bracket, double	300-9164	500	76 x 80	1000	8	500	1000




BA3-420 Pole bracket, triple	300-9165	500	76 x 80	1000	10	500	1000
------------------------------	----------	-----	---------	------	----	-----	------




Wall and pole brackets DA

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DA0-500 Wall bracket, single	300-9150	510	70		650	5.70	510	650




DA1-500 Pole bracket, single	300-9151	510		76 x 80	700	5.70	510	700
------------------------------	----------	-----	--	---------	-----	------	-----	-----




ASP530 LED

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DA2-500 Pole bracket, double	300-9152	510		76 x 80	700	8.30	510	700




DA3-500 Pole bracket, triple	300-9153	510		76 x 80	700	10.90	510	700
------------------------------	----------	-----	--	---------	-----	-------	-----	-----




Wall and pole brackets DB

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DB0-500 Wall bracket, single	300-9154	510	70		650	5.50	510	650




DB1-500 Pole bracket, single	300-9155	510		76 x 80	700	5.50	510	700
------------------------------	----------	-----	--	---------	-----	------	-----	-----




ASP530 LED

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DB2-500 Pole bracket, double	300-9156	510		76 x 80	700	7.90	510	700




DB3-500 Pole bracket, triple	300-9157	510		76 x 80	700	10.30	510	700
------------------------------	----------	-----	--	---------	-----	-------	-----	-----




Wall and pole brackets DS

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DS0-500 Wall bracket, single	300-9158	510	70		650	2.50	510	650




DS1-500 Pole bracket, single	300-9159	510		76 x 80	725	3.90	510	725
------------------------------	----------	-----	--	---------	-----	------	-----	-----




ASP530 LED

Description	Part ID	C1	C2	D × L1	H1	Weight (kg)	C	H
DS2-500 Pole bracket, double	300-9160	510		76 x 80	725	5.30	510	725




DS3-500 Pole bracket, triple	300-9161	510		76 x 80	725	6.70	510	725
------------------------------	----------	-----	--	---------	-----	------	-----	-----



Wall and pole brackets BC

Description	Part ID	C1	H1	H2	M1	Weight (kg)	C	H
BC0-420 Wall bracket, single	300-0808	460	1230	300	8	2.30	460	1230



Control

Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim® Advanced LED	430-0002

Optical Accessories

Light shield

Description	Part ID	Additional information
LS180	003-4019	Glare Shield for backlight spill. Glare Shield factory-installed or available as retrofit kit. Suitable for [S60], [S65], [S70], [R65], [P65] lenses. Must be specified at time of ordering.