


STG209 LED Stainless steel



Description

IP55, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Polycarbonate lens. Silicone rubber gasket. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Two cable entries. Pre-installation blackout is recommended for mounting in concrete, available on request.

Weight	0.00 kg
Light distribution	diffused distribution
Light source	LED-3/3W / 350 mA - 4000 K
CRI	80
Power supply	EC
LEDs	3
Rated input power	5 W
Nominal Lumen (lm)	
LED Lumen	170
Total Lumen	510
Tj	85
Rated lumens (lm)	
LED Lumen	20.6
Total Lumen	61.8
Ta	25



Specifications

Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Polycarbonate lens
Colours	Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS hardware
Ingress protection	IP55
Impact resistance	IK10
Corrosion resistance	5CE

Electrical description


Driver / Ballast	Integral EC electronic converter
------------------	----------------------------------

Additional information

Mounting Accessories

Installation blackout

Description	Part ID	A	B	C1	C
Installation blackout BST20-I	133-0075	222	109	105	105



Installation blackout BST20-II	133-0077	222	109	115	115
--------------------------------	----------	-----	-----	-----	-----

