



#### **Description**

IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation.

Integral electronic converter with DALI interface. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept.


Including 0.5 m cable with a cable connector.


Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height.

Wild-Light options available on request.

Weight	8.00 kg	
Light distribution	asymmetric, side throw [S70]	
Light source	LED-12/24W / 700 mA - 4000 K	
CRI	80	
Power supply	EC	
BUG	B1 U0 G1	
LEDs	12	
Rated input power	27 W	
Nominal Lumen (lm)		
LED Lumen	310	
Total Lumen	3720	
Tj	85	
Rated lumens (lm)		
LED Lumen	269.1	
Total Lumen	3229	
Та	25	







# **Specifications Material description**

Body Marine-grade, die-cast aluminium alloy
Lens RFC™ Reflection Free Contour main lens
Colours RAL9004 Signal black

RAL9007 Grey aluminium
RAL7016 Anthracite grey
RAL9016 Traffic white

Gasket Silicone CCG® Controlled Compression Gasket
Fasteners PCS Polymer Coated Stainless Steel Hardware

Ingress protection IP66
Impact resistance IK09
Corrosion resistance 5CE

### **Electrical description**

Driver / Ballast Integral electronic converter with DALI interface

#### **Additional information**

BUG Rating Please see individual Spec Sheets for classification of Backlight, Uplight and Glare

105-9903





## **Control**

## **R2C** Ready to Connect

Description	Part ID	
R2C Ready to Connect (top)	430-0019	