DAC220 LED





Description


IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone rubber gasket. Safety glass lens, hinged. Frame with safety catch. Two cable entries. Integral EC electronic converter in thermally separated compartment. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Factory installed LED circuit board.


2700 K option available on request.

Weight	2.90 kg
Light distribution	symmetric, very narrow beam [EE]
Light source	LED-12/24W / 700 mA - 3000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	290
	290 3480
LED Lumen	
LED Lumen Total Lumen	3480
LED Lumen Total Lumen Tj	3480
LED Lumen Total Lumen Tj Rated lumens (lm)	3480 85

DAC220 LED







Specifications Material description

Body Marine-grade die-cast aluminium alloy

Colours

RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

RAL9016 Traffic white

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP65
Impact resistance IK07

Corrosion resistance 5CE+Primer

Electrical description

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter in thermally-separated compartment

Additional information

Lifetime	Ta=40° L90B10 > 90000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

134-1426

DAC220 LED



Optical Accessories

Linear spread lens

Description	Part ID	C1
IO-180-DAC/DOC220-LED	134-1381	105



Surface wash lens

ption Part	D C1
0-DAC/DOC220-LED 134-	1440 105



134-1426

DAC220 LED



Wallwash lens

Description	Part ID	C1
IO-20-WW-DAC/DOC220-LED	134-1491	105



134-1426

DAC220 LED



Control

DALI interface

Description	Part ID	С
DALI interface	430-0013	90