



Description

IP65, Class I. IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Safety glass lens, hinged. Silicone rubber gasket.


Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC_R_ One LED Concept. Two cable entries.

Weight	2.90 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-12/24W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	12
Rated input power	27 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	3720
T _j	85
Rated lumens (lm)	
LED Lumen	274.2
Total Lumen	3290.2
T _a	25

Optical Accessories


Linear spread lens

Description	Part ID	C1
Linear spread lens IO-180	134-1381	105



Flood lens


Description	Part ID	C1
Flood lens IO-360	134-1440	105



DAC220 LED


Honeycomb louvre

Description	Part ID	C1
Honeycomb louvre IW	134-1444	105



Wallwash lens

Description	Part ID	C1
Wallwash lens IO-20	134-1491	105



Control

DALI interface

Description	Part ID	C
DALI interface	430-0013	90
