

145-0074

FLC121 LED - Wall bracket

**we-ef**



#### Description

IP55, Class I. IK07. Marine-grade, all-aluminium construction. 5CE superior corrosion protection + primer including PCS hardware. Safety glass lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter in thermally-separated compartment. Advanced thermal management protects LEDs while optimising lumens output. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Two cable entries. Knuckle permits 350° horizontal and 180° vertical aiming of optics.

|                           |                                  |
|---------------------------|----------------------------------|
| Weight                    | 2.90 kg                          |
| Light distribution        | symmetric, very narrow beam [EE] |
| Light source              | LED-6/12W / 700 mA - 4000 K      |
| CRI                       | 80                               |
| Power supply              | EC                               |
| LEDs                      | 6                                |
| Rated input power         | 14.5 W                           |
| <b>Nominal Lumen (lm)</b> |                                  |
| LED Lumen                 | 310                              |
| Total Lumen               | 1860                             |
| Tj                        | 85                               |
| <b>Rated lumens (lm)</b>  |                                  |
| LED Lumen                 | 266.6                            |
| Total Lumen               | 1599.7                           |
| Ta                        | 25                               |


#### WE-EF LIGHTING Pty Ltd

6/13 Downard Street, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 23/11/2024

## FLC121 LED - Wall bracket



## Specifications

### Material description

|                      |  |
|----------------------|--|
| Body                 | Marine-grade, die-cast aluminium alloy   |
| Lens                 | Safety glass lens  |
| Colours              | <div style="display: flex; align-items: center;"> <div style="width: 20px; height: 20px; background-color: black; margin-right: 5px;"></div> <div>RAL9004 Signal black</div> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 20px; background-color: #cccccc; margin-right: 5px;"></div> <div>RAL9006 White aluminium</div> </div> <div style="display: flex; align-items: center; margin-top: 5px;"> <div style="width: 20px; height: 20px; background-color: #808080; margin-right: 5px;"></div> <div>RAL9007 Grey aluminium</div> </div> |
| Gasket               | Silicone CCG® Controlled Compression Gasket  |
| Fasteners            | PCS Polymer Coated Stainless Steel Hardware (unpainted)  |
| Ingress protection   | IP55   |
| Impact resistance    | IK07   |
| Corrosion resistance | 5CE+Primer   |

### Electrical description

|                  |   |
|------------------|---|
| Power supply     | 230V / 50 Hz  |
| Driver / Ballast | Integral EC electronic converter in thermally-separated compartment |

### Additional information

|          |  |
|----------|--|
| Lifetime | Ta=40° L90B10 > 90000h   |
| Warranty | The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on <a href="http://www.we-ef.com">www.we-ef.com</a> for further details. |

#### WE-EF LIGHTING Pty Ltd

6/13 Downard Street, 3195 Braeside, Victoria - Phone: +61 3 8587 0444 - Fax: +61 3 8587 0499

info.australia@we-ef.com - <https://we-ef.com/aus>

Subject to technical changes and errors. - Generated on 23/11/2024

145-0074

FLC121 LED - Wall bracket

## Optical Accessories

### Snoot

| Description | Part ID  | A  | C1  |
|-------------|----------|----|-----|
| Snoot ET    | 145-0030 | 60 | 120 |



### Linear spread lens

| Description       | Part ID  | C1 |
|-------------------|----------|----|
| IO-180-FLC121-LED | 145-0050 | 81 |



**FLC121 LED - Wall bracket**

**Surface wash lens**

---

| Description       | Part ID  | C1 |
|-------------------|----------|----|
| IO-360-FLC121-LED | 145-9390 | 81 |

---



---

**Honeycomb louvre**

---

| Description   | Part ID  | C1 |
|---------------|----------|----|
| IW-FLC121-LED | 145-0143 | 81 |

---



**FLC121 LED - Wall bracket**

**Wallwash lens**

| Description         | Part ID  | C1 |
|---------------------|----------|----|
| IO-20-WW-FLC121-LED | 145-0145 | 81 |



**Glare shield**

| Description     | Part ID  | A   | C1  |
|-----------------|----------|-----|-----|
| Glare shield ES | 145-9192 | 102 | 119 |



145-0074

**we-ef**

**FLC121 LED - Wall bracket**

**Linear louvre**

---

| Description      | Part ID  | C1 |
|------------------|----------|----|
| Linear louvre IL | 145-9171 | 81 |

---

