#### FLC121 LED #1





#### **Description**


IP66, Class I. IK07. Marine-grade die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens. PMMA-LED lens array. Remote 240v gear to be ordered separately.


2700 K option available on request.

Weight	1.70 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-6/12W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	14.5 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	1860
_Tj	85
Rated lumens (lm)	
LED Lumen	287
Total Lumen	1721.8
Та	25

# 145-0127 FLC121 LED #1

# we-ef





#### FLC121 LED #1



# **Specifications Material description**

Body Marine-grade die-cast aluminium alloy

Lens Safety glass lens

Colours RAL9004 Signal black

RAL9006 White aluminium
RAL9007 Grey aluminium

Gasket Silicone CCG® Controlled Compression Gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP66
Impact resistance IK07

Corrosion resistance 5CE+Primer

## **Electrical description**

## **Additional information**


Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details.

## **FLC121 LED #1**



# **Optical Accessories**

## Snoot



# Linear spread lens

Description	otion Part ID	C1
		81



## **FLC121 LED #1**



## **Surface wash lens**

Description	Part ID	C1
IO-360-FLC121-LED	145-9390	81



# Honeycomb louvre

Description	Part ID	C1
IW-FLC121-LED	145-0143	81




#### **FLC121 LED #1**




## Wallwash lens

Description	Part ID	C1
IO-20-WW-FLC121-LED	145-0145	81



# Glare shield



## **FLC121 LED #1**



# **Mounting Accessories**

# **Ground spike EF**

Description	Part ID	H1	Weight (kg)
Ground spike EF1	310-9102	270	1.20

