




Description

IP55, Class I. IK10. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection + primer including PCS hardware. Polycarbonate lens. Silicone rubber gasket.
Integral EC electronic converter. CAD-optimised lens for superior illumination and glare control.

Weight	9.10 kg
Light distribution	symmetric distribution [C60]
Light source	LED-FT-17W / 500 mA - 4000 K
CRI	80
Power supply	EC
LEDs	1
Rated input power	20 W
Rated lumens (lm)	
LED Lumen	1942.2
Total Lumen	1942.2
Ta	25
Nominal Lumen (lm)	
LED Lumen	3200
Total Lumen	3200
Tc	25



Specifications
Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	Polycarbonate lens
Colours	RAL9004 Signal black RAL9006 White aluminium RAL9007 Grey aluminium
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP55
Impact resistance	IK10
Corrosion resistance	5CE+Primer
Windage	0.147 m ²

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Power factor	> 0.9
Surge protection	In-pole surge protection SP10 device supplied. Please refer to WE-EF installation instructions for details. Use suffix +A for Integral surge protection.

Additional information

Lifetime	Ta=40° L70B50 > 50000h
Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details.

Control


Eco Step Dim® Basic

Description	Part ID
Eco Step Dim® Basic LED	430-0001


Mounting Accessories

Wall and pole brackets AZ

Description	Part ID	C1	D1	D2	D × L1	H1	H2	M1	Weight (kg)	C	H
AZ0-400 Wall bracket, single	155-0266	400	275	235		350	275	12	4	400	270




AZ20-400 Pole bracket, double	155-0304	400			76 x 80	390		7		400	270
-------------------------------	----------	-----	--	--	---------	-----	--	---	--	-----	-----



ZA640-FT LED

Description	Part ID	C1	D1	D2	D × L1	H1	H2	M1	Weight (kg)	C	H
AZ30-400 Pole bracket, triple	155-0306	400			76 x 80	390			9.80	400	270



Optical Accessories

Light shield

Description	Part ID	H1
LS180-[C60]	159-0321	120

