

Description

IP66, Class I. Class II on request. IK08. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone CCG® Controlled Compression Gasket. RFC® Reflection Free Contour main lens. Integral EC electronic converter in thermally separated compartment. DALI. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. Factory installed LED circuit board. The luminaire is factory-sealed and does not need to be opened during installation.


Optional 2200 K version up to max. 1050mA available. To be specified at time of ordering.


Eco Step Dim[®] up to 1050 mA on request.

Brackets to be ordered separately.

Photometric files (IES, LDT) for light distributions [S60] [S65] [S70] [R65] [P65] [A60] with Backlight Shield on request.

Weight	15.00 kg	
Light distribution	asymmetric, side throw [S70]	
Light source	LED-24/48W / 700 mA - 4000 K	
CRI	80	
Power supply	EC	
LEDs	24	
Rated input power	54 W	
Nominal Lumen (Im)		
LED Lumen	310	
Total Lumen	7440	
Тј	85	
Rated lumens (lm)		
LED Lumen	274.4	
Total Lumen	6585.8	
Та	25	





Specifications Material description

Body	Marine-grade, die-cast aluminium alloy
Lens	RFC [®] Reflection Free Contour technology
Colours	RAL9004 Signal black
	RAL9006 White aluminium
	RAL9007 Grey aluminium
	RAL7016 Anthracite grey
	RAL9016 Traffic white
Gasket	Silicone CCG [®] Controlled Compression Gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware
Ingress protection	IP66
Impact resistance	IK08
Corrosion resistance	5CE
Windage	0.23

Electrical description

Power supply	220-240V / 50-60 Hz
Driver / Ballast	Integral EC electronic converter. DALI
Power factor	> 0.9
Surge protection	6/6 kV (optional SP10)

PFL540 LED



Additional information

Lifetime	Ta=25° L90B10 > 90000h
Energy efficiency class	C-D (Light source)

PFL540 LED

Control

Eco Step Dim[®] Basic


Description	Part ID
Eco Step Dim [®] Basic LED	430-0001

Eco Step Dim® Advanced

Description	Part ID
Eco Step Dim [®] Advanced LED	430-0002

Eco Step Dim[®] Motion

Description	Part ID
Eco Step Dim [®] Motion - Linked	430-0021



R2C Ready to Connect

Description	Part ID
R2C Ready to Connect (top)	430-0019
R2C Ready to Connect (below)	430-0027
R2C Ready to Connect (top and below)	430-0032

we-ef

PFL540 LED

Citygrid Motion On Pole



Description	Part ID	Additional information
Citygrid Motion - Entry-Package 420-0011	420-0011	Citygrid Motion. Das All-in-One Gerät, das vorhandene Leuchten in ein intelligentes Lichtsystem verwandeln kann.
		Einstiegs-Paket WE-EF liefert und konfiguriert Leuchten und Citygrid System einmalig ab Werk bzw. am Einsatzort. Neukonfiguration als Service abrufbar (kostenpflichtig). Gateway/App nicht inbegriffen.
		Anwendungen: Kommunale Einzelprojekte, Insellösungen und Feldversuche für Smart Lighting, z.B. einzelne Straßen, Wege oder Plätze. Halböffentliche oder private Projekte, z.E Firmengelände, Parkplatz.



Description	Part ID	Additional information
Citygrid Motion - Standalone-Package 420-00	420-0012	Citygrid Motion On Pole Controller. The Citygrid Motion On Pole Controller is the all-in-one device that can convert existing luminaires into an intelligent lighting system.
		The standalone package: Dongle & apps included; operators can configure, change and service the Citygrid system themselves (on site) using the apps on their mobile device. Applications: demarcated communal projects (street, square, district) or private projects (larger company sites, commercial estates) if qualified personnel are available for the
		operation of the system.



Description	Part ID	Additional information
Citygrid Motion - Smart-City-Package	420-0013	Citygrid Motion On Pole Controller
		The Citygrid Motin On Pole Controller is the all-in-one device that can convert existing
		luminaires into an intelligent lighting system.
		The Smart-City package:
		Internet gateway (via mobile phone) and dashboard included; operators can configure,
		change and service themselves (remotely). Networked Smart-City functions (data collection
		remote maintenance, etc.).
		Applications: larger communal projects or field trials in the context of Smart City; operator has qualified personnel (municipal utilities).

PFL540 LED

we-ef

Citygrid Motion On Luminaire

Description	Part ID	Additional information
Citygrid Motion - Entry-Package	420-0021	Citygrid On Luminaire - Entry PackageCitygrid On Luminaire. Die Sensoren erkennen Bewegung und Verkehr beim Betreten des Sensor und Leuchtenfelds.
		Einstiegs-Paket WE-EF liefert und konfiguriert Leuchten und Citygrid System einmalig ab Werk bzw. am Einsatzort. Neukonfiguration als Service abrufbar (kostenpflichtig). Gateway/App nicht inbegriffen.
		Anwendungen: Kommunale Einzelprojekte, Insellösungen und Feldversuche für Smart Lighting, z.B. einzelne Straßen, Wege oder Plätze. Halböffentliche oder private Projekte, z.E Firmengelände, Parkplatz.Citygrid built-in light controller with angled sensors The sensors detect motion and traffic on entering the sensor and lighting field.
		The entry-level package: WE-EF supplies and configures luminaires and the Citygrid system once ex works or on site Reconfiguration is available as a service (chargeable). Gateway/app not included.
		Applications: individual communal projects, isolated solutions and field trials for smart lighting, e.g. single streets, paths or squares. Semi-public or private projects, e.g. company site, car park.

we-ef

Description	Part ID	Additional information
Citygrid Motion - Standalone-Package	420-0022	Citygrid Motion built-in light controller with angled sensors The sensors detect motion and traffic on entering the sensor and lighting field.
		The standalone package: Dongle & apps included; operators can configure, change and service the Citygrid system themselves (on site) using the apps on their mobile device. Applications: demarcated communal projects (street, square, district) or private projects (larger company sites, commercial estates) if qualified personnel are available for the operation of the system.





Description	Part ID	Additional information
Citygrid Motion - Smart-City-Package	420-0023	Citygrid Motion built-in light controller with angled sensors The sensors detect motion and traffic on entering the sensor and lighting field.
		The Smart-City package: Internet gateway (via mobile phone) and dashboard included; operators can configure, change and service themselves (remotely). Networked Smart-City functions (data collection, remote maintenance, etc.). Applications: larger communal projects or field trials in the context of Smart City; operator has qualified personnel (municipal utilities).

PFL540 LED

Citygrid Motion Zhaga



Description	Part ID	Additional information
itygrid Motion - Standalone-Package	420-0032	Citygrid Motion Zhaga controller with sensor. The compact all-in-one design turns every luminaire with a Zhaga Book 18 socket facing the street surface into motion-controlled, intelligent street & area lighting.
		The standalone package: Dongle & apps included; operators can configure, change and service the Citygrid system themselves (on site) using the apps on their mobile device.
		Applications: demarcated communal projects (street, square, district) or private projects (larger company sites, commercial estates) if qualified personnel are available for the operation of the system.



Description	Part ID	Additional information
Citygrid Motion - Smart-City-Package	420-0033	Citygrid Motion Zhaga controller with sensor. The compact all-in-one design turns every luminaire with a Zhaga Book 18 socket facing the street surface into motion-controlled, intelligent street & area lighting.
		The Smart-City package: Internet gateway (via mobile phone) and dashboard included; operators can configure, change and service themselves (remotely). Networked Smart-City functions (data collection, remote maintenance, etc.). Applications: larger communal projects or field trials in the context of Smart City; operator has qualified personnel (municipal utilities).

PFL540 LED



Wild-Light Citygrid Motion On Pole

Description	Part ID	Additional information
Wild-Light Citygrid Motion - Entry-	420-1111	Citygrid Motion On Pole Controller.
Package		The Citygrid Motion On Pole Controller is the all-in-one device that can convert existing
		luminaires into an intelligent lighting system.
		The entry-level package:
		WE-EF supplies and configures luminaires and the Citygrid system once ex works or on site.
		Reconfiguration is available as a service (chargeable). Gateway/app not included.
		Applications: individual communal projects, isolated solutions and field trials for smart lighting, e.g. single streets, paths or squares. Semi-public or private projects, e.g. company
		site, car park.

we-ef	F
-------	---

Description	Part ID	Additional information			
Wild-Light Citygrid Motion -	420-1112	Citygrid Motion On Pole Controller for Wild-Light.			
tandalone-Package		The Citygrid Motion On Pole Controller is the all-in-one device that can convert existing			
		luminaires into an intelligent lighting system.			
		The standalone package:			
		Dongle & apps included; operators can configure, change and service the Citygrid system			
		themselves (on site) using the apps on their mobile device.			
		Applications: demarcated communal projects (street, square, district) or private projects (larger company sites, commercial estates) if qualified personnel are available for the operation of the system.			



Description	Part ID	Additional information					
Wild-Light Citygrid Motion - Smart-	420-1113	Citygrid Motion On Pole Controller for Wild-Light.					
City-Package		The Citygrid Motion On Pole Controller is the all-in-one device that can convert existing					
		luminaires into an intelligent lighting system.					
		The Smart-City package:					
		Internet gateway (via mobile phone) and dashboard included; operators can configure,					
		change and service themselves (remotely). Networked Smart-City functions (data collection remote maintenance, etc.).					
		Applications: larger communal projects or field trials in the context of Smart City; operator					
		has qualified personnel (municipal utilities).					

PFL540 LED

Mounting Accessories


Wall and pole brackets RV


Description	Part ID	Addition Gal information	C2	С3	D1	D× L1	H1	H2	M1	M2	Weigh (kg)	it C	D	Η
RV0 Wall bracket	108-0979	RVO 108 Wall bracket	100	60			200	160	38	12	2.00	108		
		C2 M1 H2 E M2 U C3	1 H	1	C1									
RV2-76 Pole bracket, double	108-0980	147				76 x 100					4.80	147	76	200
		D x L1-												





Description	Part ID	Addition Cal information	C2	С3	D1	D × L1	H1	H2	M1	M2	Weigh (kg)	t C	D	Η
RV2-60 Pole bracket, double	108-0981	147				60 x					4.80	147	60	200
						100								






PFL540 LED



Post top fitter AKV

Description	Part ID	C1	D × L1	D × L2	H1	Weight (kg)
AKV2-76	300-0053	180	76x100	67x	235	1.50



PFL540 LED

Optical Accessories

Light shield

Description	Part ID	Additional information
LS180-[A60]	430-0038	Light shield LS180 to greatly reduce or eliminate light pollution. PA injection moulded component, black matt. Suitable for asymmetric light distribution [A60].
LS180	430-0029	Glare Shield for backlight spill. Glare Shield factory-installed or available as retrofit kit. Suitable for [S60], [S65], [S70], [R65], [P65] lenses. Must be specified at time of ordering.