

#### **Description**

Anti-Slip ceramic Coating. ASC Lens light loss factor = 14.25%.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Cable gland with spiral cable bending protection. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Factory-installed circuit board with High Efficiency LEDs. 0-10V Dimming comes standard with luminaire. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

Suitable for flush installation in concrete or earth. The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black)

+ XXX-XXXX (Accessory 1)

Weight	18.20 lb
Light distribution	symmetric, very narrow beam, 'sharp cut-off' [VNS]
Light source	LED-12/18W / 500 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	12
Rated input power	21 W
Nominal Lumen (lm)	
LED Lumen	184.8
Total Lumen	2217
Tj	85
Delivered lumens (lm)	
LED Lumen	141.4
Total Lumen	1697
Та	25

### **ETC130-GB LED ASC**





# **Specifications**

## **Material description**

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5

Tonnes

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

### **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Driver / Ballast Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Termination Factory sealed termination chamber

Surge protection Integral 10kV Surge Protector

#### Additional information

Lifetime	Ta=25°/40° L90B10 > 90000h
D: .	0.40)/

Dimming 0-10V available in request. Must be factory fitted.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.