

#### **Description**

Anti-Slip ceramic Coating.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10). Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Factory-installed circuit board with High Efficiency LEDs. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black).

+ XXX-XXXX (Accessory 1)

Weight	15.00 lb
Light distribution	linear spread, medium beam [M]
Light source	LED-12/12W / 350 mA - 3000 K
CRI	80
Power supply	electronic gear
LEDs	12
Rated input power	14 W
Nominal Lumen (lm)	
LED Lumen	134.5
Total Lumen	1614
Tj	85
Delivered lumens (lm)	
LED Lumen	93.5
Total Lumen	1122.4
Та	25

#### **ETC330-GB LED ASC**





# **Specifications**

### **Material description**

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5

tonnes

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

## **Electrical description**

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Termination Factory sealed termination chamber

### **Additional information**

Ambient Temperature Ta less than 25 deg. C

Dimming 0-10V available in request. Must be factory fitted.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.