

Description

Anti-Slip ceramic Coating.

IP69K. Class I. IK10+. Stainless steel construction. PCS hardware. Anti-Slip ceramic Coating ASC to DIN 51130 (Trip Classification 10). Silicone CCG® Controlled Compression Gasket. Safety glass lens; max load 5.5 tons (11,000 lbs). Luminaire can be driven over at low speed. Factory-sealed termination chamber complete with cable gland and 3 ft of flexible PVC-free, gel-impregnated anti-wicking cable. Factory-installed circuit board with High Efficiency LEDs. Gimbal mounted, 360° rotatable and 30° tiltable. 'No tool' removable gear/lens tray.

The concrete-pour installation blockout is supplied as standard with luminaire.


Specify product with 7 Digit product code - Finish Color. Accessories, such as mounting, optical, and electrical, must be specified separately.


Example: XXX-XXXX-9004 (Black).

+ XXX-XXXX (Accessory 1)

Weight15.00 lbLight distributionlinear spread, very narrow beam, 'sharp cut-off'Light sourceLED-12/12W / 350 mA - 4000 KCRI80Power supplyelectronic gearLEDs12Rated input power14 WNominal Lumen (Im)LED Lumen134.5Total Lumen1614Tj85Delivered lumens (Im)LED Lumen91.1Total Lumen1093.5Ta25		
Light source LED-12/12W / 350 mA - 4000 K CRI 80 Power supply electronic gear LEDs 12 Rated input power 14 W Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Weight	15.00 lb
CRI 80 Power supply electronic gear LEDs 12 Rated input power 14 W Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Light distribution	
Power supply electronic gear LEDs 12 Rated input power 14 W Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Light source	LED-12/12W / 350 mA - 4000 K
LEDs 12 Rated input power 14 W Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	CRI	80
Rated input power 14 W Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Power supply	electronic gear
Nominal Lumen (Im) LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	LEDs	12
LED Lumen 134.5 Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Rated input power	14 W
Total Lumen 1614 Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5		
Tj 85 Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5	Nominal Lumen (lm)	
Delivered lumens (Im) LED Lumen 91.1 Total Lumen 1093.5		134.5
LED Lumen 91.1 Total Lumen 1093.5	LED Lumen	
Total Lumen 1093.5	LED Lumen Total Lumen	1614
	LED Lumen Total Lumen Tj	1614
Ta 25	LED Lumen Total Lumen Tj Delivered lumens (lm)	1614 85
	LED Lumen Total Lumen Tj Delivered lumens (Im) LED Lumen	1614 85 91.1

ETC330-GB LED ASC





Specifications

Material description

Body Luminaire body constructed of deep drawn stainless steel. Outer housing composite material.

Lens 5/8 in thick Antislip Coating ASC tempered glass lens (Slip Resistance Class R10), max load 5

tonnes

Colors Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS polymer coated stainless steel

Ingress protection IP69K - HIGHEST PROTECTION RATING AVAILABLE

Impact resistance IK10+
Corrosion resistance 5CE

Electrical description

Power supply Integral [ECG] electronic driver 120V-277V. 0-10V dimmable, to be specified with order.

Termination Factory sealed termination chamber

Additional information

Ambient Temperature Ta less than 25 deg. C

Dimming 0-10V available in request. Must be factory fitted.

Listings ETL, UL-1598, CSA-C22.2#250.0. Suitable for Wet Locations.