



Description

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface (6 W luminaires only) available on request.

Luminaire installation blockout and sealable junction box included in supply.

2700 K option available on request.

ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch **here.**

Weight	4.00 kg
Light distribution	symmetric, very narrow beam [EE]

Light source LED-3/6W / 700 mA - 4000 K

CRI 80

Power supply EC

LEDs 3

Rated input power 7.5 W

Nominal Lumen (lm)

LED Lumen 310

Total Lumen 930



T_j 85

Rated lumens (lm)

LED Lumen 231.9

Total Lumen 695.6

T_a 25



Specifications

Material description

Body	Stainless steel construction
Lens	Safety glass lens, max. load 5 tonnes
Colours	 Stainless Steel
Gasket	Silicone rubber gasket
Fasteners	PCS Polymer Coated Stainless Steel Hardware (unpainted)
Ingress protection	IP67
Impact resistance	IK10+

Electrical description

Power supply	230V / 50 Hz
Driver / Ballast	Integral EC electronic converter
Termination	Junction box supplied

Additional information

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.
----------	--

Mounting Accessories

Installation cover

Description	Part ID	C1
Installation cover BE	185-0796	160




C1

Optical Accessories

Honeycomb louvre


Description	Part ID	C1
Honeycomb Louvre	185-2869	60



— C1 —

Linear spread lens


Description	Part ID	C1
Linear spread lens IO-180	185-9612	60



— C1 —

Surface wash lens

Description	Part ID	Additional information
Flood lens I0-360	185-9613	60

**Linear louvre**

Description	Part ID	Additional information	Part ID
Linear louvre LL for 120-GB LED	185-9614	ETC320	60



Colour filter

Description	Part ID
Colour filter IF	on request

