



#### **Description**

IP67. IK10+. Stainless steel construction including PCS hardware. Safety glass lens, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Anti-wick technology, equipped with a cable gland and 0.5 meters of flexible, PVC-free cable.

Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised optics for superior illumination and glare control. OLC® One LED Concept. 20° tiltable and 355° rotatable. 1-10 V analogue dimming or DALI interface available on request.

Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.


ASC Anti Slip Coating on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https://vimeo.com/672613058">here.</a></strong>

Weight	8.00 kg
Light distribution	symmetric, very narrow beam, sharp cut-off [EES]
Light source	LED-6/12W / 700 mA - 4000 K
CRI	80
Power supply	EC
LEDs	6
Rated input power	14.5 W
Nominal Lumen (lm)	
LED Lumen	310
Total Lumen	1860
Tj	85
Rated lumens (lm)	
LED Lumen	289.5
Total Lumen	1736.8
Та	25







# **Specifications**

### **Material description**

Body Stainless steel construction

Lens Safety glass lens, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+

### **Electrical description**


Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

Termination Junction box supplied

#### **Additional information**

Warranty	The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement
	located on www.we-ef.com for further details. Warranty void if installed without proper
	drainage.






# **Mounting Accessories**

### **Installation cover**

Description	Part ID	C1
Installation cover BE	185-0325	250



C1





# **Optical Accessories**

# **Optical Adaptor**

Description	Part ID
Internal optical Adaptor IA	185-7420



### **Linear louvre**

Description	Part ID	C1
Linear louvre IL	185-9677	81





### ETC330-GB LED

## **Linear spread lens**

Description	Part ID	C1
Linear spread lens IO-180	185-9678	98



### **Surface wash lens**

Description	Part ID	C1
Flood lens IO-360	185-9679	98



### 185-7229



### ETC330-GB LED

### **Colour filter**

Description	Part ID	
Colour filter IF	on request	

