



#### **Description**

IP67, Class I. IK10+. Stainless steel construction including PCS hardware. Safety glass lens with opal diffuser, max. load 5 tonnes. Luminaire can be driven over at low speed. Silicone rubber gasket. Complete with cable gland and 0.5 m of flexible PVC-free cable.


Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. Luminaire installation blockout and sealable junction box included in supply.


2700 K option available on request.

IMPORTANT! Inground blockouts must be installed with effective drainage, watch <strong><a href="https://vimeo.com/672613058">here.</a></strong>

| Weight             | 3.80 kg                          |
|--------------------|----------------------------------|
| Light distribution | symmetric, diffused distribution |
| Light source       | LED-3/6W / 700 mA - 4000 K       |
| CRI                | 80                               |
| Power supply       | EC                               |
| LEDs               | 3                                |
| Rated input power  | 7.5 W                            |
| Nominal Lumen (lm) |                                  |
| LED Lumen          | 310                              |
| Total Lumen        | 930                              |
| Tj                 | 85                               |
| Rated lumens (lm)  |                                  |
| LED Lumen          | 70.2                             |
| Total Lumen        | 210.6                            |
| Та                 | 25                               |
|                    |                                  |







## **Specifications**

### **Material description**

Body Stainless steel construction

Lens Safety glass lens with opal diffuser, max. load 5 tonnes

Colours

Stainless Steel

Gasket Silicone rubber gasket

Fasteners PCS Polymer Coated Stainless Steel Hardware (unpainted)

Ingress protection IP67
Impact resistance IK10+


#### **Electrical description**

Power supply 230V / 50 Hz

Driver / Ballast Integral EC electronic converter

#### Additional information

Warranty The product is supplied with 10-year warranty. Please refer to the LED Warranty Statement located on www.we-ef.com for further details. Warranty void if installed without proper drainage.





# **Mounting Accessories**

#### **Installation cover**

| Description           | Part ID  | C1  |
|-----------------------|----------|-----|
| Installation cover BE | 185-0796 | 160 |



WE-EF LIGHTING Pty Ltd